

**PRODUCT DATASHEET****GDK-400**

Grounding Kit for 4" HELICABLE™ HJA400-50A Air-Dielectric Coaxial Cable

HELICABLE™ Grounding Kit Copper Strap & Bonding Wire for HJA400-50-A Air-dielectric cable

FEATURES**• Installation**

HELICABLE™ Grounding Kit for Quick and easy installation

• Electrical Protection

HELICABLE™ Grounding Kit have Low contact transition resistance

• Environmental Protection

HELICABLE™ Grounding Kit is Weatherproof

GDK-158 for
4" HELICABLE™ HJA400-50-A
Air-Dielectric Coaxial Cable**Technical Details****GENERAL SPECIFICATIONS**

| | | |
|------------------------|--|------------------------------|
| Product Line | | Coaxial Cable Accessories |
| Product Type | | Copper Strap & Bonding Wire |
| Transmission Line Type | | HJA400-50A |
| Cable Type | | Air-Dielectric Coaxial Cable |
| Cable Size | | 4" |

MECHANICAL SPECIFICATION

| | | |
|-----------------------|-----------------|---|
| Material | | Ground Strap, Bonding Conductor Wire : Copper Screw, Flat Washer, Spring Washer, Nut : Stainless Steel |
| Bonding Wire Diameter | mm ² | 16 |
| Bonding Wire Length | mm (in) | 1500 (59) |
| Lug Type | | Two-hole |
| Lug Hole Size | | M6 |
| Screw Size | in | 3/8 x 1 |

ELECTRICAL SPECIFICATION

| | | |
|-------------------------------|----|----|
| Contact transition resistance | mΩ | ≤5 |
|-------------------------------|----|----|

ENVIRONMENTAL SPECIFICATION

| | | |
|--------------------------|---------|---------------------------|
| Working Temperature | °C (°F) | -40 to 70 (-40 to 158) |
| Storage Temperature | °C (°F) | -40 to 70 (-40 to 158) |
| Weatherproofing Method | | Butyl and electrical Tape |
| Weatherproofing Standard | | IP68 |

PACKING INFORMATION

| | | |
|------------------------|---------|--|
| Packing Quantity | pcs | 1 in plastic bag |
| Included | | Grounding Kit, 3/8" x 1" screw, 3/8" spring washer, 3/8" flat washer, 3/8" nut |
| Weight, gross | kg | 0.65 |
| Dimensions (H x W x L) | Mm (in) | 155 x 305 x 355 (6.1 x 12 x 14) |